DISPLAYS2GO

Wall Mounting Instructions

NOTE: Screws and anchors for mounting the bulletin board to concrete wall is provided. Due to different constructions and safety requirements, choose appropriate hardware for the bulletin board. If you are not sure, please consult local hareware store or have a contractor to mount the board.







Choose desired location and height to mount the board. Use a bubble level to help.
Screw the Z-brackets to the wall. Distance between the brackets (X) should be equal to the distance between the mounting plate on the back of the notice board (Y).





3. Lift the noticeboard over and hook the mounting plates (B) over the Z-brackets (A) as shown in (Fig. A).





4. Align L-Bracket to the holes underneath the noticeboard and mark the position on the wall.



5. Remove the noticeboard. Align the L-Bracket with the marked position. Screw the L-Bracket into the wall.



secure the board on the wall.





IMPORTANT:

This unit requires **2 PERSON LIFT**

DISPLAYS2GO

Attaching Showcase Lock



Slide both doors to the left.
Slide the notched bar over the rear glass door as shown.



2. Fasten the screw on the back of the notched bar. NOTE: DO NOT overtighten the screws.



3. Slide the front door over the notched bar. Slide both doors to the closed position



4. Slide the lock over the notched bar. Make sure the flat edge rest against the edge of the outside door.



If you have any questions regarding our products, please visit us at www.displays2go.com or contact D2G customer service at 844-221-3388.