

CLEAR  DIGITAL



Müv^{Pro}

M Ü V Y O U R M E S S A G E

**Introducing the Clear Digital™
Müv Pro, a new way to elevate
engagement with your audience
and streamline interactive
processes with ease.**

Stunning Visuals: 27" TFT LED Touchscreen Display

Powerful Performance: Android14 OS

Effortless Mobility: Low-Profile Mobile Base

Brilliant Versatility: Supports Portrait and Landscape

getcleardigital.com



Panel	Panel Size: 24" x 13.9" x .55" Display Area: 23.5" (H) x 13.2" (V) Resolution: 3840 (H) x 2160 (V) Aspect Ratio: 16:9 Pixel Pitch: 0.1554 x 0.1554	Brightness: 350 cd/m ² Viewing Angle: 89/89/89/89 Response Time: G to G: 8MS Contrast Ratio: 1000:1 Screen Weight: 2.35 kg Lamp Type: WLED
Power	Main Power: 12 V	Consumption: 35W
Android	CPU: 8 CORE (RK3576) Up to 2.2 GHz GPU: ARM G52 MC3 RAM: 4GB ROM: 32GB	OS: Android 14 Wi-Fi: Built-in Wi-Fi 802.11 a/b/g/n/ac/ax LAN: 1000M
Connector	USB: 3.0 x2 HDMI IN: x1 HDMI OUT: x1 RJ45: x1	LAN: x1 TF Card: x1 Type-C: x1 Audio: 3.5 mm x1
Sound	Built-in Speakers: 2x5 W	
Battery	Run time: 13 hours	
Remote	Control Mode: Bluetooth Voice function: Support	Gyroscope: Support Effective distance: >8 m
Size	Machine Size: 51" x 12.6"/20.1" x 20.1" (1295x320/510x510mm) Machine Weight: 51.8 lbs (23.5kg) Gross Weight: 62.8lbs (28.5kg)	Packaging Dimensions: 51" x 20.1" x 20.1" (1295mm x 510mm x 510mm) Box Weight: 80.2lbs (36.4 kg)
Functions	Decoding resolution: 2160P UHD compatible Playback mode: Yes	Touch support: Yes
Accessories	Remote Control (1), Power supply (1), User Manual (1), Keys, Screws, Optional colored silicone bumpers, Optional 100mm, 75mm VESA mounting plate, Optional Scanner-Printer-Camera Combo	
File Support	Video: VP9,H.265 4K60, H.264 4K30, (AVS/AVS+, VP8, MPEG1, MPEG2, MPEG4, XVID, H263, SorenSpark, MJPEG, 1080P)	Image: JPG, BMP, PNG Audio: MP3, OGG, FLAC, APE, AAC AMR, WAV, DSD, G729, ALAC, ATRAC, OPUS
Other	Regulatory Approvals: CE, FCC, ROHS VESA Mounting: Display cannot be VESA mounted, but does have available Mini PC VESA Mount accessories.	Warranty: 2 years