

MODEL: A-10K71-SD

DISPLAYS2GO

POWER BANK (10000mAh)



USER MANUAL

How to charge your device



3 A MAX OUTPUT
Standard USB port

OUT 5V 2.4A(max)

IN/OUT 5V 3A(max)

Compatible with

Most Mobile Phones
Other 5V Digital Devices

1. Choose the appropriate output terminal for your device.
2. Connect the device to the appropriate output terminal of the POWER BANK using the USB connection cable.
3. To begin charging, press and release the power button.

How to charge 'Power Bank'



Electrical Adapter



Powered Computer USB port

Support 5V-3A(MAX) input

IN 5V 2A

IN/OUT 5V 3A(max)

1. Use the Micro USB / Type-C port to charge the power bank
2. Connect the USB connector to your adapter or computer USB port.

LED status guide

Capacity: 100%-75%-50%-25%-0%
4-----3-----2-----1----- LEDs on

Charging your device:

The LEDs will indicate the current capacity

Charging your POWER BANK:

The LEDs will be flashing to show charging status

"This Product falls under e-waste (Management) Rules, 2016.
For proper disposal method, visit our website."



If you have any questions regarding our products, please visit us at
www.displays2go.com or contact D2G customer service at 844-221-3388.