# LW20S2 Assembly Instructions

Place metal base face down and screw in all (4) wheels by hand or with provided wrench, then flip base and lock wheels.

Once metal base is right side up, place base pole with round bottom on top of the center of the base, lining up the holes.

Place in all (4) bolts with "48" label on top, and screw in with one of the provided wrenches.

Once base pole is secured to the base, slide in the adjustable height pole to the top of the base pole, ensuring the openings are on the same side as pictured.

Insert the large of two knobs into the opening pictured and put adjustable height pole at desired level. Line up both poles and twist the knob all the way in.

Separately, place the shelve face down, and then place the shelf mount bracket on top of it, lining up the holes. Make sure the part of the shelf mount bracket with two holes (enlarged image) is on the proper side in accordance with the lip side.

Screw in short bolts to secure shelf mount bracket.

Line the shelf up on top of the pole, making sure the two pictured sides line up.

Use the pictured nut and bolt to secure the base through the upper hole and tighten with provided wrench. Please note the shelf will be attached at this point but still loose.

Twist in knob to lower hole. This knob can be loosened to adjust tilt surface of the display.

Place shelf top face down, and line up bracket mount with predrilled holes, and then use short screws to put it in place.

Line up shelf bracket and secondary bracket piece anywhere on pole, then use four bolts and wing nuts to secure into place. Shelf height can be adjusted at any time.

Place the second shelf top face down, and line up bracket mount with predrilled holes. Place washers on top of the holes, and then use long screws to put it in place.

Second shelf: Line up shelf bracket and secondary bracket anywhere on pole, then use four bolts and wing nuts to secure into place. Shelf height can be adjusted at any time.

Your stand is now complete!