

IMPORTANT

Please take time to read all instructions before start installing the unit. Be sure you fully understand all the steps needed to finish the installation.

**Operating Instructions**

- (1) Open battery compartment cover at the bottom of the lid to insert 6 AA batteries correctly with regard to polarity then replace battery cover.
- (2) Turn the power switch on at the back, then the indicator will turn red for 3 seconds. It will flash every 3 seconds to indicate the system is on and ready to use.
- (3) Hover your hand or any object above the sensor within 6 inches and the lid will open. The lid will then close after five seconds of inactivity. The lid will remain open when there is an object in the sensor zone.
- (4) When the trash bin is full, press the "open" button at the induction window to keep the lid open. It is in order to deal with the frequent switch trash bin. Press the "close" button to close the lid, and then the circuit resumes its automatic induction function.
- (5) When there is no activity, The light will flash every 3 seconds. When the cover is open, the indicator light will turn solid green. When the cover is closing, the indicator light will turn red. When you use manual open-cover function, the indicator will flash in green every 3 seconds.
- (6) If the indicator flashes in yellow every 3 seconds, it indicates the battery level is low. New batteries can last about 3 months if the lid opens and closes around 20 times per day,.

Scan QR code to visit
the product page:



If you have any questions regarding our products, please visit us at www.displays2go.com or contact D2G customer service 844-221-3388.