

Spec Sheet

TexStyles® Mosaic

Graphic Fabrics

Recommended Processes  **Dye Sublimation, UV & Latex Inks**

Applications Include: Digital Imaging, Trade Show Banners, Table Cover, Roll-up Banners, Retail POP/POS, Interior Decoration, Specialty Print Applications

Key Features of TexStyles® Mosaic Graphic Fabrics

- 100% Woven Polyester
- Wrinkle Resistant
- Exceptional Whiteness
- Vivid Color Reproductions
- Very Stable with Minimal Shrinkage
- Meets all Standards Coast-to-Coast for Flame Resistance

TexStyles® are stocked in widths up to 122 inches and can be trimmed to meet your width and roll length requirements. Sample rolls are available to ensure suitability for each customer's application.

TexStyles® Graphic Fabrics		
Physical Property	Standard	Method of Testing
Material	100% Woven Polyester	
Weight	5.8 oz/yd ²	ASTM D-3776-09
Width	Various	ASTM D-3774
Tensile Strength - Length	284 (lbf)	ASTM D-5034-09
Tensile Strength - Width	332 (lbf)	ASTM D-5034-09
Elongation - Length	44% at break	ASTM D-5034-09
Elongation - Width	51% at break	ASTM D-5034-09
Lightness	91	CIE L*
Light Transmission / Opacity	47% (@ 100ft candles)	AATCC 148-1989
Flame Resistance	Passed	NFPA 701-2010
Flame Resistance	Passed	NY / NJ Port Authority
Flame Resistance	Passed	Boston City Fire Codes

Suitability for use is at the sole determination of the user. All values represent averages. Textiles are subject to certain production variances for weight, color, width and physical properties. In order to ensure that the product desired is acceptable, the customer should request a small sample to determine its compatibility for use.