

# Orbus Saturn Truss Kit



DISPLAYS2GO

OESAKIT

- Kit includes:
- 16 x 6-way junction boxes
  - 4 x 24" straight truss lengths
  - 16 x 36" straight truss lengths
  - 12 x 46" straight truss lengths
  - 1 x full set of quicklock connectors
  - 2 x adjustable tabletops
  - 5 x 50 watt spotlights
  - 2 x OCF molded cases

Fits in a 10' x 20' space

Refer to related graphic template for specific information on sizes and bleeds.



We are continually improving and modifying our product range and reserve the right to vary the specifications without prior notice. All dimensions and weights quoted are approximate and we accept no responsibility for variance. E&OE. See Graphic Templates for graphic bleed specifications.


SATURN PIECE COUNT:




OR-J-3  
16




OR-J-DBL  
0



OR-24-2  
4



OR-30-2  
0




OR-36-2  
16



OR-46-2  
12




OR-45-CV-3  
0



OR-90-CV-2  
0



OR-B90  
0



OR-B90A  
0



OR-B45  
0



OR-TOOL-B  
2



OR-QL-T2J  
42



OR-QL-T2T  
14




OR-UC-QL  
0




OR-STG  
0



OR-LCD1-B  
0



OR-LCD2-B  
0



OR-LCD3-B  
0



SPOTLIGHT  
5



OR-TBL  
2



OR-TBL2-L  
0



OR-TBL2-R  
0



OR-IS-24 0



OR-IS-36 0



OR-IS-46 0



OR-IS-48 0



OR-CIS-90  
0



OR-SE-IS-90  
0












OR-CIS-45  
0










OR-ATL-CNTR  
0


SATURN TABLETOP ACCESSORY PIECE COUNT:



SATURN CASE COUNT:



SATURN GRAPHIC SPECS:  
DYE SUBLIMATION



**Acceptable File formats:**

Illustrator CS6 or below  
Photoshop CS6 or below  
Art time will be charged if files need to be fixed or altered to meet guidelines. When sending files please be sure to include all support art (fonts, linked images, etc.)

**Font Specifications:**

Fonts must be converted to outlines.

**Bleeds:**

All orbital truss graphics require specific bleeds. The sizes listed above represent the finished graphic size. Please keep all logos, type and critical information at least 1" in from each edge of the finished graphic.

**Dye Sublimation:** 2" bleed around the perimeter.

**Color:**

All files are printed as CMYK format. All critical Pantone colors need to be called out in the file or specified on the order as Coated or Uncoated swatches.

**Resolution:**

All raster files (either print files or linked files) must be at 100-120 pixels per inch at 100%

**Finishing Details:**

When graphics are notched, a 7/8" square is cut in the appropriate location.

**FS:** Graphics mounted to front of truss system

**BS:** Graphics mounted to back of truss system

Dye Sublimation graphics are attached to truss with velcro.

**To ensure quality, please note:**


Each graphic has a specific code or number located on the graphic. The electronic print files provided must be named accordingly. Using this coding system will allow us to preflight and prepare your files for print more efficiently. **If you fail to provide your graphic files in this format, additional charges may be necessary to complete your printed materials.**

SATURN FLOOR PLAN:


SCALE REF = 5ft



10' d X 20' w Inline



SATURN COLOR CODED PARTS:



Parts exploded

